

High Speed Thread Lubricant - X80 & X50

X80 High Speed Thread Lubricant is an advanced technology lubricant and sewing aid especially formulated for use with PTFE coated fiberglass sewing thread. Extensive testing in actual production environments has resulted in a thread lubricant that provides excellent friction reduction for cooler needle operations. 99% of our lubricated thread is made with X80 lube.

X50 lubricating qualities are similar in a lighter lubricant formulated with waxes and oils. X50 is not as "slick" a lubricant, but works well for some applications.

In either case, our in-line lubricating process ensures complete, uniform penetration of the fiber bundle versus others immersion method, which may result in spotty penetration or messy residual lubricant in the final package. Contact W.F. Lake Corp. for additional information or samples for testing;.

Features

High Speed Lubricant
Formulated for PTFE/Fiberglass
Uniform penetration
Extensive In-Use Testing

Benefits

Excellent Friction Reduction
Cooler Needle Operation
Enhanced "Sewability"

Physical & Chemical Properties

Product Designation:	X80	X50
Form	-----Liquid Applied to Thread -----	
Appearance	----- Clear, Water White -----	
Color Stability	-----Excellent -----	
Resistance to Degradation	Excellent	Good
Lubrication Properties	Excellent	Good
Solubility	Dissolves in many solvents, NOT water soluble	
Application Method	In-line application after PTFE coating	
Product Designation	Suffix "L" added to part number (ex. R753-12L, X80)	

X50 & X80 Thread Lubricants are available on all of W.F. Lake Corp's. high temperature sewing threads, including PTFE coated fiberglass, S-2 Glass, Quartz, Kevlar and all of our stainless steel wire inserted threads as well.

W.F. Lake Corp.

P.O. Box 4214

65 Park Road

Glens Falls, NY 12804

Customer Service: (800) 428-1162

Tel: (518) 798-9934

Fax: (518) 798-9936

www.wflake.com

1000 deg. Fahrenheit



540 deg. Celsius

*Available with
X50 or X80
High Speed Lubricant*

Applications:

High Temperature Textiles
Safety Spray Shields
Filter Bags
Braided Sleeving
Insulation Jackets
Thermal Insulation Pads
High Temperature Gaskets
Kiln Seals
Fire Resistant Composites
Welding Blankets
Heat Shields



W.F. LAKE

High Performance PTFE & Silicone Coated Products

W.F. Lake Corp. manufactures high performance PTFE and Silicone coated products designed for extreme operating environments. Our non-stick, temperature and chemical resistant materials are uniquely suited for a wide variety of specialized industrial applications in a number of diverse industries. By combining our broad based in-house processing and converting capabilities, we are able to offer you creatively engineered products especially suited to your application. Give us a call to discuss your material needs... we're ready to help!

***We manufacture the industry's widest range of
PTFE Coated Fiberglass products !***



PTFE Coated ...

Fabrics

Adhesive Tapes

S-2 Glass Fabrics

Kevlar Fabrics*

High Temperature Belting

Braided Draw Cords

Braided Lacing Tapes

Yarns

E-Glass Sewing Thread

S-2 Glass Sewing Thread (1400 deg. F)

Kevlar Sewing Thread*

Quartz Sewing Threads (2000 deg F !!!)

W.F. LAKE CORP., 65 Park Road, Glens Falls, NY 12804

Tel: (518) 798-9934 . Tel: (800) 428-1162. Fax: (518) 798-9936. E-mail: info@wflake.com

www.wflake.com



High Performance PTFE & Silicone Coated Products