



High Performance PTFE & Silicone Coated Products

## ***PTFE Coated Beta (BC) Fiberglass Sewing Thread***

1000 deg. Fahrenheit  
540 deg. Celsius



| Product Data                                                                                                                                                                                                                                                                                                                                                              |                                               |         |         |         |         |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|---------|---------|---------|---------|---------|
| Product #                                                                                                                                                                                                                                                                                                                                                                 | R751-12                                       | R751-18 | R753-12 | R753-18 | R753-24 | R753-27 |
| Thread Style                                                                                                                                                                                                                                                                                                                                                              | - Continuous Filament Beta (BC) Glass Fiber - |         |         |         |         |         |
| Coating Type                                                                                                                                                                                                                                                                                                                                                              | -PTFE, Sintered-                              |         |         |         |         |         |
| Coating %                                                                                                                                                                                                                                                                                                                                                                 | 18                                            | 18      | 12      | 12      | 12      | 12      |
| Yield (yds/lb)                                                                                                                                                                                                                                                                                                                                                            | 2850                                          | 1900    | 3000    | 2000    | 1500    | 1050    |
| Tensile (lbs)                                                                                                                                                                                                                                                                                                                                                             | 12                                            | 18      | 12      | 18      | 25      | 30      |
| Diameter (nom)                                                                                                                                                                                                                                                                                                                                                            | 0.016"                                        | 0.019"  | 0.015"  | 0.018"  | 0.021"  | 0.024"  |
| Final Twist                                                                                                                                                                                                                                                                                                                                                               | "Z"                                           | "Z"     | "Z"     | "Z"     | "Z"     | "Z"     |
| Color                                                                                                                                                                                                                                                                                                                                                                     | -Natural, Tan-                                |         |         |         |         |         |
| <div><div>Serving Package: King Spool</div><div>Operating Temp: 1000 deg. F. (540 deg. C.)</div><div>Approx. Net Wt.: 2 lb/spool (others available)</div><div>(PTFE Coating to 600 deg. F)</div><div>Available with high speed silicone thread lubricant applied in line.</div><div>All values are typical and should not be used for writing specifications.</div></div> |                                               |         |         |         |         |         |

***W.F. Lake Corp.***

P.O. Box 4214  
65 Park Road  
Glens Falls, NY 12804  
Customer Service: (800) 428-1162  
Tel: (518) 798-9934  
Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)  
[info@wflake.com](mailto:info@wflake.com)