




High Performance PTFE & Silicone Coated Products

PTFE Coated Fiberglass Lacing Tape and Tie Cord

1000 deg. Fahrenheit - Fiberglass
 550 deg. Fahrenheit - PTFE



538 deg. Celsius - Fiberglass
 288 deg. Celsius - PTFE



Product Data								
Product #	-E779 Series-					-E761 Series-		
	-222	-303	-476	-680	-1075	-314	-668	-1330
Coating Type	- PTFE, Unsintered -							
Braid Type	-Flat-					-Round-		
Yield (yds/lb)	220	325	520	430	1025	360	540	1150
Thickness (in.)	.018	.015	.011	.013	.007	n/a	n/a	n/a
Width (in.)	1/8	7/64	3/32	5/64	3/64	n/a	n/a	n/a
Diameter (in.)	n/a	n/a	n/a	n/a	n/a	.047	.034	.027
Tensile (lb/min)	150	125	90	60	40	80	75	50
Package Size (yds)	-250 or 500 yard spools-							
<p>Elongation of lacing tape and tie cord is typically less than 5%. Operating Temps. 1000 deg. F -Fiberglass / 550 deg. F -PTFE</p> <p>Colors other than natural may require minimum purchase quantity. Please consult the factory.</p> <p>Dimensions shown are nominal, however most are within 10%. Consult factory as needed.</p>								

W.F. Lake Corp.
 P.O. Box 4214
 65 Park Road
 Glens Falls, NY 12804

Customer Service: (800) 428-1162
 Phone: (518) 798-9934
 Fax: (518) 798-9936