


## PTFE Coated Fiberglass Lacing Tape and Tie Cord

1000 deg. Fahrenheit - Fiberglass  
550 deg. Fahrenheit - PTFE



538 deg. Celsius - Fiberglass  
288 deg. Celsius - PTFE



<b>Product Data</b>								
Product #	<b>-E779 Series-</b>					<b>-E761 Series-</b>		
	-222	-303	<b>-476</b>	-680	-1075	-314	-668	-1330
Coating Type	- PTFE, Unsintered -							
Braid Type	-Flat-					-Round-		
Yield (yds/lb)	220	325	<b>520</b>	430	1025	360	540	1150
Thickness (in.)	.018	.015	<b>.011</b>	.013	.007	n/a	n/a	n/a
Width (in.)	1/8	7/64	<b>3/32</b>	5/64	3/64	n/a	n/a	n/a
Diameter (in.)	n/a	n/a	<b>n/a</b>	n/a	n/a	.047	.034	.027
Tensile (lb/min)	150	125	<b>90</b>	60	40	80	75	50
Package Size (yds)	-250 or 500 yard spools-							
<p><b>Elongation</b> of lacing tape and tie cord is typically less than 5%. <b>Operating Temps.</b> 1000 deg. F -Fiberglass / 550 deg. F -PTFE</p> <p><b>Colors</b> other than natural may require minimum purchase quantity. Please consult the factory.</p> <p><b>Dimensions</b> shown are nominal, however most are within 10%. Consult factory as needed.</p>								

**W.F. Lake Corp.**  
P.O. Box 4214  
65 Park Road  
Glens Falls, NY 12804

Customer Service: (800) 428-1162  
Phone: (518) 798-9934  
Fax: (518) 798-9936