



High Performance PTFE & Silicone Coated Products

L11-Series PTFE Coated Fiberglass Fabric

"High Build" Grade



Product Data				
Product #	L11-3	L11-5	L11-6	L11-10
Base Fabric	1080	2116	2116	7628
Thickness (in)	0.003"	0.005"	0.006"	0.010"
Weight (yds/lb)	0.30	0.50	0.58	0.99
Coating %	70	60	65	65
Tensile (yds/in)	65	100	100	200
Color	-Natural, Tan-			
<p>Elongation of fiberglass fabrics is less than 5%</p> <p>Operating Temperature: Min -200 to Max 550 deg. F, Intermittent to 600 deg. F.</p> <p>Thickness shown is nominal, however, most fabrics are +/- 10%.</p> <p>Widths are standard at 38". Other typical widths include 41" & 48". Slit rolls available. Please consult the factory or W.F. Lake Corp. literature for available alternatives.</p> <p>Values are typical and should not be used for writing specifications.</p> <p>All data is subject to change without notice.</p>				

W.F. Lake Corp.
P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936

www.wflake.com
info@wflake.com