


PTFE Coated Aramid* / Stainless Thread

500 deg. Fahrenheit - Kevlar
 1000 deg. Fahrenheit –Stainless Steel Wire



260 deg. Celsius - Kevlar
 538 deg. Celsius – Stainless Steel Wire



Product Data				
Product #	R722-70	R721-71	R721-73	R721-710
Thread Style	- S-2 Glass Fiber with integral Stainless Steel Wire -			
Coating Type	-PTFE, Sintered-			
Stainless Steel Wire	No Wire	1 wire	3 wires	10 wires
Coating %	12	12	12	12
Yield (yds/lb)	5000	4500	3000	1450
Tensile (lbs)	25	25	25	25
Diameter (nom)	0.010"	0.011"	0.014"	0.024"
Final Twist	"Z"	"Z"	"Z"	"Z"
Color	-Natural, Tan-			
Serving Package: King Spool		Operating Temp: Kevlar to 500 deg. F		
Approx. Net Wt.: 1 lb/spool (others available)		(Stainless Steel wire to over 1000 deg. F)		
Available with high speed silicone thread lubricant applied in line.				
All values are typical and should not be used for writing specifications. *Kevlar Reg. DuPont				

W.F. Lake Corp.

P.O. Box 4214
 65 Park Road
 Glens Falls, NY 12804
 Customer Service: (800) 428-1162
 Tel: (518) 798-9934
 Fax: (518) 798-9936

www.wflake.com
info@wflake.com