



High Performance PTFE & Silicone Coated Products

PTFE Coated "E-Glass" Fiberglass Sewing Thread

1000 deg. Fahrenheit
540 deg. Celsius



Product Data				
Product #	R783-12	R783-18	R783-24	R783-27
Thread Style	- Continuous Filament "E-Glass Fiber -			
Coating Type	-PTFE, Sintered-			
Coating %	12	12	12	12
Yield (yds/lb)	3000	2000	1500	1050
Tensile (lbs)	12	18	25	30
Diameter (nom)	0.015"	0.018"	0.021"	0.024"
Final Twist	"Z"	"Z"	"Z"	"Z"
Color	-Natural, Tan-			
Serving Package: King Spool Operating Temp: 550 deg. Continuous, 1000 deg. F. intermittent. Approx. Net Wt.: 2 lb/spool (others available) (290 deg. C continuous) , (540 deg. C intermittent) Available with high speed silicone thread lubricant applied in line. All values are typical and should not be used for writing specifications.				

W.F. Lake Corp.
 P.O. Box 4214
 65 Park Road
 Glens Falls, NY 12804
 Customer Service: (800) 428-1162
 Tel: (518) 798-9934
 Fax: (518) 798-9936

www.wflake.com
info@wflake.com