


PTFE Coated Quartz Sewing Thread

2000 deg. Fahrenheit - Fiberglass
550 deg. Fahrenheit - PTFE



1100 deg. Celsius - Fiberglass
288 deg. Celsius - PTFE



Product Data					
Product #	TFQ-12	TFQ-18	TFQ-24	TFQ-27	TFQ-30
Thread Style	- Continuous Filament Pure Fused Silica -				
Coating Type	-PTFE, Sintered-				
Coating %	20	20	20	20	20
Yield (yds/lb)	2950	1975	1475	920	635
Tensile (lbs)	12	20	24	27	30
Diameter (nom)	0.014"	0.017"	0.021"	0.024"	0.028"
Final Twist	"Z"	"Z"	"Z"	"Z"	"Z"
Color	-Natural, Tan-				
Serving Package: King Spool			Operating Temp: 2000 deg. F. (538 deg. C.)		
Approx. Net Wt.: 1 lb/spool (others available)			(PTFE Coating to 550 deg. F)		
Available with high speed silicone thread lubricant applied in line.					
All values are typical and should not be used for writing specifications.					

W.F. Lake Corp.

P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936

www.wflake.com
info@wflake.com