


## ***PTFE Coated SGT-243I(L) Inconel Steel High Temperature Fiberglass Sewing Thread***

1400 deg. Fahrenheit - Fiberglass  
2000 deg. Fahrenheit - Inconel



760 deg. Celsius - Fiberglass  
1093 deg. Celsius - Inconel



<b><i>Product Data</i></b>	
<b>Product #</b>	<b>SGT-243I ("L" suffix indicates X80 lube)</b>
<b>Thread Style</b>	<b>- Twisted S-2 Glass Fiber with 3 Ends Inconel Wire -</b>
<b>Coating Type</b>	<b>-PTFE, Sintered-</b>
<b>Coating %</b>	<b>12% Nominal</b>
<b>Yield (yds/lb)</b>	<b>1000 yds/lb</b>
<b>Tensile (lbs)</b>	<b>25 lbs min</b>
<b>Diameter (nom)</b>	<b>0.024"</b>
<b>Elongation</b>	<b>&lt; 5%</b>
<b>Color</b>	<b>-Natural, Tan-</b>
<b>Serving Package:</b> King Spool <b>Operating Temp:</b> 1400 deg. F. (760 deg. C.) <b>Approx. Net Wt.:</b> 2 lb/spool (others available)                      (PTFE Coating to 600 deg. F) Available with high speed silicone thread lubricant applied in line. <b>All values are typical and should not be used for writing specifications.</b>	

***W.F. Lake Corp.***

P.O. Box 4214  
65 Park Road  
Glens Falls, NY 12804  
Customer Service: (800) 428-1162  
Tel: (518) 798-9934  
Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)  
[info@wflake.com](mailto:info@wflake.com)