

PTFE Coated Fiberglass Part Numbers

15T

55 -

190

3

WHT

Coating Percentage (nominal)

12T 12% PTFE
15T 15% PTFE

Coating Type

01. Unsintered, Natural
04. Sintered, Natural
25. Nomex
51. Unsintered, Natural, Blk, Brwn
52. Sintered, heat cleaned colors
54. Sintered, Natural, BLK, BRN
55. Unsintered, heat cleaned colors or white

Yarn Size

-032 150 2/2
-043 150 1/3
-064 150 1/2
-096 225 1/2
-190 450 1/2

Number of Ends Up:
X = 7005 tube: (1 end bulk)
Braider Tubes:
1, 2, 3, 4,
5, 6, 7, 8 ends.

Color:

NAT = Natural WHT = White
BLU = Blue GRN = Green
RED = Red YLW = Yellow
BLK = Black BRN = Brown
GRY = Gray VLT = Violet
ORG = Orange

Example: 15T55-1903WHT.

* 15% PTFE coating / unsintered, heat cleaned 450 1/2, packaged 3 ends on a braider tube, white.

Braider Packages Available

Package Descr.	# ends (type)	approx. wt. per tube (lbs)	Inside Dia.(in)	Length (inches)	Max OD (inches)
Pkg #47 Braider bobbin	1-10	1/3 lb	5/8"	4 1/4"	2"
Pkg #4035 Braider bobbin	1 - 10	1/2 lb	5/8"	5 1/4"	2"

Other packages are available for certain yarns. Please contact the factory for details. All values subject to change without notice.

W.F. Lake Corp.
P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936

www.wflake.com



Standards / Specifications:
Mil-STD-1285
High Temp.: Mil-W-7139
Munsell ANSI/EIA-359-A
Mil Std- 104



W.F. LAKE

High Performance PTFE & Silicone Coated Products