



High Performance PTFE & Silicone Coated Products

PTFE Coated Beta (BC) Fiberglass Sewing Thread

1000 deg. Fahrenheit
540 deg. Celsius

R753-24 meets

Mil-C-20079 Type 3, Class 3



Product Data						
Product #	R751-12	R751-18	R753-12	R753-18	R753-24	R753-27
Thread Style	- Continuous Filament Beta (BC) Glass Fiber -					
Coating Type	-PTFE, Sintered-					
Coating %	18	18	12	12	12	12
Yield (yds/lb)	2850	1900	3000	2000	1500	1050
Tensile (lbs)	12	18	12	18	25	30
Diameter (nom)	0.016"	0.019"	0.015"	0.018"	0.021"	0.024"
Final Twist	"Z"	"Z"	"Z"	"Z"	"Z"	"Z"
Color	-Natural, Tan-					
Serving Package: King Spool			Operating Temp: 1000 deg. F. (540 deg. C.)			
Approx. Net Wt.: 2 lb/spool (others available)			(PTFE Coating to 600 deg. F)			
Available with high speed silicone thread lubricant applied in line.						
All values are typical and should not be used for writing specifications.						

W.F. Lake Corp.

P.O. Box 4214

65 Park Road

Glens Falls, NY 12804

Customer Service: (800) 428-1162

Tel: (518) 798-9934

Fax: (518) 798-9936

www.wflake.com

info@wflake.com