




High Performance PTFE & Silicone Coated Products

## PTFE Coated Fiberglass Lacing Tape and Tie Cord

1000 deg. Fahrenheit - Fiberglass  
 550 deg. Fahrenheit - PTFE



538 deg. Celsius - Fiberglass  
 288 deg. Celsius - PTFE



<b>Product Data</b>								
Product #	<b>-E779 Series-</b>					<b>-E761 Series-</b>		
	<b>-222</b>	<b>-303</b>	<b>-476</b>	<b>-680</b>	<b>-1075</b>	<b>-314</b>	<b>-668</b>	<b>-1330</b>
<b>Coating Type</b>	- PTFE, Unsintered -							
<b>Braid Type</b>	-Flat-					-Round-		
<b>Yield (yds/lb)</b>	220	325	520	430	1025	<b>360</b>	540	1150
<b>Thickness (in.)</b>	.018	.015	.011	.013	.007	<b>n/a</b>	n/a	n/a
<b>Width (in.)</b>	1/8	7/64	3/32	5/64	3/64	<b>n/a</b>	n/a	n/a
<b>Diameter (in.)</b>	n/a	n/a	n/a	n/a	n/a	<b>.047</b>	.034	.027
<b>Tensile (lb/min)</b>	150	125	90	60	40	<b>80</b>	75	50
<b>Package Size (yds)</b>	-250 or 500 yard spools-							
<p><b>Elongation</b> of lacing tape and tie cord is typically less than 5%. <b>Operating Temps.</b> 1000 deg. F -Fiberglass / 550 deg. F -PTFE</p> <p><b>Colors</b> other than natural may require minimum purchase quantity. Please consult the factory.  <b>Dimensions</b> shown are nominal, however most are within 10%. Consult factory as needed.</p>								

**W.F. Lake Corp.**  
 P.O. Box 4214  
 65 Park Road  
 Glens Falls, NY 12804

Customer Service: (800) 428-1162  
 Phone: (518) 798-9934  
 Fax: (518) 798-9936