


## **L12-Series PTFE Coated Fiberglass Fabric**

### **Mechanical Grade**

575 deg. Fahrenheit



302 deg. Celsius



<b>Product Data</b>				
<b>Product #</b>	<b>L12-3</b>	<b>L12-5</b>	<b>L12-6</b>	<b>L12-10</b>
<b>Base Fabric</b>	1080	2116	2116	7628
<b>Thickness (in)</b>	0.003"	0.0045"	0.005"	0.008"
<b>Weight (yds/lb)</b>	0.20	0.37	0.44	0.75
<b>Coating %</b>	50	45	55	50
<b>Tensile (warp)</b>	70	120	120	220
<b>Tensile (fill)</b>	50	100	100	175
<b>Color</b>	-Natural, Tan-			
<p><b>Elongation</b> of fiberglass fabrics is less than 5%</p> <p><b>Operating Temperature:</b> Min -200 to Max 550 deg. F, Intermittent to 600 deg. F.</p> <p><b>Thickness</b> shown is nominal, however, most fabrics are +/- 10%.</p> <p><b>Widths</b> are standard at 38". Other typical widths include 41", 50", 60", 82".</p> <p>Please consult the factory or W.F. Lake Corp. literature for available alternatives.</p> <p><b>Values are typical and should not be used for writing specifications.</b></p> <p><b>All data is subject to change without notice.</b></p>				

**W.F. Lake Corp.**

P.O. Box 4214

65 Park Road

Glens Falls, NY 12804

Customer Service: (800) 428-1162

Tel: (518) 798-9934

Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)

[info@wflake.com](mailto:info@wflake.com)