


L14-Series PTFE Coated Fiberglass Fabric

“Semi-Conductive” Grade

575 deg. Fahrenheit



302 deg. Celsius



Product Data				
Product #	L14-3	L14-5	L14-6	L14-10
Base Fabric	1080	2116	2116	7628
Thickness (in)	0.003”	0.005”	0.006”	0.010”
Weight (yds/lb)	0.27	0.44	0.54	0.90
Coating %	67	55	63	60
Tensile (warp)	70	120	120	225
Tensile (fill)	50	100	100	175
Tear Strength (lbs)	10	20	20	35
Color	-Natural, Tan-			
<p>Elongation of fiberglass fabrics is less than 5%</p> <p>Operating Temperature: Min -200 to Max 550 deg. F, Intermittent to 600 deg. F.</p> <p>Thickness shown is nominal, however, most fabrics are +/- 10%.</p> <p>Widths are standard at 38”. Other typical widths include 41”, 50”, 60”, 82”.</p> <p>Please consult the factory or W.F. Lake Corp. literature for available alternatives.</p> <p>Values are typical and should not be used for writing specifications.</p> <p>All data is subject to change without notice.</p>				

W.F. Lake Corp.

P.O. Box 4214

65 Park Road

Glens Falls, NY 12804

Customer Service: (800) 428-1162

Tel: (518) 798-9934

Fax: (518) 798-9936

www.wflake.com

info@wflake.com