




High Performance PTFE & Silicone Coated Products

PTFE Coated "E-Glass" Fiberglass Sewing Thread

1000 deg. Fahrenheit - Fiberglass
550 deg. Fahrenheit - PTFE



538 deg. Celsius - Fiberglass
288 deg. Celsius - PTFE



Product Data			
Product #	R753-12	R753-18	R753-24
Thread Style	- Continuous Filament Beta (BC) Fiber -		
Coating Type	-PTFE, Sintered-		
Coating %	15	15	15
Yield (yds/lb)	3000	2000	1500
Tensile (lbs)	12	18	25
Diameter (nom)	0.015"	0.018"	0.021"
Final Twist	"Z"	"Z"	"Z"
Color	-Red, Blue, Green, Orange, Black, Brown-		
Serving Package: King Spool		Operating Temp: 1000 deg. F. (540 deg. C.)	
Approx. Net Wt.: 2 lb/spool (others available)		(PTFE Coating to 600 deg. F)	
Available with high speed silicone thread lubricant applied in line.			
All values are typical and should not be used for writing specifications.			
PN Example: R753-18LRED: X80 Lubricated, Red Color Thread			

W.F. Lake Corp.
P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936

www.wflake.com
info@wflake.com