


## PTFE Coated Quartz Sewing Thread

2000 deg. Fahrenheit - Quartz  
550 deg. Fahrenheit - PTFE



1100 deg. Celsius - Quartz  
288 deg. Celsius - PTFE



<b>Product Data</b>					
<b>Product #</b>	<b>TFQ-12</b>	<b>TFQ-18</b>	<b>TFQ-24</b>	<b>TFQ-27</b>	<b>TFQ-30</b>
<b>Thread Style</b>	- Continuous Filament Pure Fused Silica -				
<b>Coating Type</b>	-PTFE, Sintered-				
<b>Coating %</b>	20	20	20	20	20
<b>Yield (yds/lb)</b>	2950	1975	1475	920	635
<b>Tensile (lbs)</b>	7	20	24	27	30
<b>Diameter (nom)</b>	0.014"	0.017"	0.021"	0.024"	0.028"
<b>Final Twist</b>	"Z"	"Z"	"Z"	"Z"	"Z"
<b>Color</b>	-Natural, Tan-				
<b>Serving Package:</b> King Spool			<b>Operating Temp:</b> 200 deg. F. (538 deg. C.)		
<b>Approx. Net Wt.:</b> 1 lb/spool (others available)			(PTFE Coating to 550 deg. F)		
Available with high speed silicone thread lubricant applied in line.					
<b>All values are typical and should not be used for writing specifications.</b>					

**W.F. Lake Corp.**

P.O. Box 4214  
65 Park Road  
Glens Falls, NY 12804  
Customer Service: (800) 428-1162  
Tel: (518) 798-9934  
Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)  
[info@wflake.com](mailto:info@wflake.com)