




High Performance PTFE & Silicone Coated Products

PTFE Coated Para-Aramid / Stainless Thread

500 deg. Fahrenheit – Para-Aramid
 1600 deg. Fahrenheit –Stainless Steel Wire



260 deg. Celsius – Para-Aramid
 870 deg. Celsius – Stainless Steel Wire



Product Data					
Product #	R722-70	R722-80	R721-71	R721-73	R721-710
Thread Style	- Para-Aramid* Continuous Filament -				
Coating Type	-PTFE, Sintered-				
Stainless Steel Wire	No Wire	No Wire	1 wire	3 wires	10 wires
Min. Coating %	12	12	12	12	12
Yield (yds/lb)	5400	4100	4700	3500	1500
Tensile (lbs)	25	30	25	25	40
Diameter (nom)	0.012"	0.015"	0.012"	0.015"	0.018"
Final Twist	"Z"	"Z"	"Z"	"Z"	"Z"
Color	-Natural, Yellow/Gold-				
Serving Package: King Spool		Operating Temp: Para-Aramid to 500 deg. F			
Approx. Net Wt.: 1 lb/spool (others available)		(Stainless Steel wire to over 1600 deg. F)			
Available with high speed silicone thread lubricant applied in line.					
All values are typical and should not be used for writing specifications.					

W.F. Lake Corp.
 P.O. Box 4214
 65 Park Road
 Glens Falls, NY 12804
 Customer Service: (800) 428-1162
 Tel: (518) 798-9934
 Fax: (518) 798-9936

www.wflake.com
info@wflake.com