

# **BC-18BLK**

## **High Temperature Fiberglass Sewing Thread**

### **Features**

High Temperature Resistance  
 High Strength  
 Finest Glass Fiber Available  
 Acrylic bonded  
 Excellent Flexibility

### **Benefits**

Chemical Resistance  
 Excellent Thermal Shock Resistance  
 Flexibility

**W.F. Lake Corp.**  
 P.O. Box 4214  
 65 Park Road  
 Glens Falls, NY 12804  
 Customer Service: (800) 428-1162  
 Tel: (518) 798-9934  
 Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)

### **PRODUCT DATA: BC6-BLK**

<b>Product #</b>	<b>BC-6BLK</b>
<b>Thread Style</b>	Twisted BC-6 Glass Fiber
<b>Coating Type</b>	Acrylic Bonded
<b>Yield (yds/lb)</b>	1900 yds (4736m/kg)
<b>Tensile (lbs)</b>	18 lbs min.
<b>Diameter (nom)</b>	0.019" nominal
<b>Elongation</b>	< 5%
<b>Color</b>	Black
<b>Operating Temperature</b>	530 C / 1000 F
<p><b>Serving Package:</b> King Spool  <b>Approx. Net Wt.:</b> 2 lb/spool (others packages available.)  <b>Available with high speed silicone thread lubricant applied in line.</b>  <b>All values are typical and should not be used for writing specifications.</b></p>	

1000 deg. Fahrenheit



530 deg. Celsius

### **Applications:**

High Temperature Textiles  
 Safety Spray Shields  
 Braided Sleeving  
 Insulation Jackets  
 Thermal Insulation Pads  
 High Temperature Gaskets  
 Kiln Seals  
 Welding Blankets  
 Heat Shields



# **W.F. LAKE**

*High Performance PTFE & Silicone Coated Products*