




High Performance PTFE & Silicone Coated Products

## PTFE Coated Quartz Tie Cord

2000 deg. Fahrenheit - Fiberglass  
 550 deg. Fahrenheit - PTFE



1075 deg. Celsius - Fiberglass  
 288 deg. Celsius - PTFE



<b>Product Data</b>	
<b>Product #</b>	<b>Q761-540</b>
<b>Coating Type</b>	- PTFE, Unsintered -
<b>Braid Type</b>	-Round-
<b>Yield (yds/lb)</b>	345
<b>Thickness (in.)</b>	n/a
<b>Width (in.)</b>	n/a
<b>Diameter (in.)</b>	.050
<b>Tensile (lb/min)</b>	65
<b>Package Size (yds)</b>	250 Yds
<p><b>Elongation</b> of tie cord is typically less than 5%. <b>Operating Temps.</b> 2000 deg. F –Fiberglass / 550 deg. F –PTFE</p> <p><b>Colors</b> other than natural may require minimum purchase quantity. Approx. 25% tensile strength loss with colors. Please consult the factory.</p> <p><b>Dimensions</b> shown are nominal, however most are within 10%. Consult factory as needed.</p>	

**W.F. Lake Corp.**  
 P.O. Box 4214  
 65 Park Road  
 Glens Falls, NY 12804

Customer Service: (800) 428-1162  
 Phone: (518) 798-9934  
 Fax: (518) 798-9936