


## PTFE Coated “E-Glass” Fiberglass Sewing Thread

1000 deg. Fahrenheit



538 deg. Celsius - Fiberglass



<b>Product Data</b>			
<b>Product #</b>	<b>R783-12</b>	<b>R783-18</b>	<b>R783-24</b>
<b>Thread Style</b>	- Continuous Filament “E-Glass Fiber -		
<b>Coating Type</b>	-PTFE, Sintered-		
<b>Coating %</b>	12	12	12
<b>Yield (yds/lb)</b>	3000	2000	1500
<b>Tensile (lbs)</b>	12	18	25
<b>Diameter (nom)</b>	0.015”	0.018”	0.021”
<b>Final Twist</b>	“Z”	“Z”	“Z”
<b>Color</b>	-Natural, Tan-		
<b>Serving Package:</b> King Spool <b>Operating Temp:</b> 550 deg. Continuous, 1000 deg. F. intermittent. <b>Approx. Net Wt.:</b> 2 lb/spool (others available)    (290 deg. C continuous) , (540 deg. C intermittent) Available with high speed silicone thread lubricant applied in line. <b>All values are typical and should not be used for writing specifications.</b>			

**W.F. Lake Corp.**

P.O. Box 4214  
 65 Park Road  
 Glens Falls, NY 12804  
 Customer Service: (800) 428-1162  
 Tel: (518) 798-9934  
 Fax: (518) 798-9936

[www.wflake.com](http://www.wflake.com)  
[info@wflake.com](mailto:info@wflake.com)