



# W.F. LAKE

High Performance PTFE & Silicone Coated Products

## PTFE Coated Para-Aramid\*/ Stainless Steel Thread

W.F. Lake Corp. manufactures its PTFE coated ParaAramid\*/ Stainless Steel Wire Sewing Thread from individually coated, continuous filament para-aramid yarns and fine stainless steel wire, making one of the strongest high temperature sewing threads on the market today. Each individual para-aramid yarn is completely coated with black pigmented PTFE prior to twisting. Once they are twisted together, the thread is again coated with black pigmented PTFE, dramatically improving UV resistance and contaminant resistance while reducing friction. In addition, the smooth coating improves handling characteristics and reduces the tendency of uncoated Kevlar\* thread to fray, abrade and clog sewing equipment.

### Features

- High Temperature
- High Strength
- Individually PTFE Coated Input Yarns
- Uniform PTFE Final Coat
- Light Weight
- Balanced Twist
- 1 End Stainless Steel Wire

### Benefits

- Chemical Resistance
- Minimal Buildup of contaminants
- Easy Sewing vs. other high temperature threads
- Enhanced UV Resistance
- Excellent Thermal Cycling
- Highly Flexible
- Fatigue Resistance

### Product Data

<b>Product Number</b>	<b>R721-71BLK</b>
<b>Base Thread Style</b>	Para-aramid (Kevlar*) with Stainless Steel (Individually PTFE coated continuous filament yarns)
<b>Stainless Steel Wire</b>	1 end of stainless steel wire
<b>Coating Type</b>	Black PTFE, Sintered
<b>Coating Percentage (PTFE nom.)</b>	30%
<b>Yield (yards/lb nom.)</b>	3,800
<b>Tensile Strength (lbs. min.)</b>	25
<b>Diameter (nom. inch)</b>	0.013"
<b>Final Twist</b>	"Z"
<b>Color</b>	----- Black -----

Serving Package: King Spool

Approx. Net Wt.: 1 lb/spool (others available)

Available with high speed silicone thread lubricant applied in line.

All values are typical and should not be used for writing specifications. \*Kevlar Reg. DuPont

Operating Temp: Kevlar to 400 deg. F.

(Stainless Steel wire to over 1000 deg. F.)

### W.F. Lake Corp.

P.O. Box 4214

65 Park Road

Glens Falls, NY 12804

Customer Service: (800) 428-1162

Tel: (518) 798-9934

Fax: (518) 798-9936

info@wflake.com



### Applications:

- Safety Spray Shields
- High Temperature Textiles
- Multi-Layer Insulation
- Filter Media
- Welding Curtains
- Kiln Seals
- High Temperature Gaskets

### Important Processing Information.

W.F. Lake Corp. PTFE coated fiberglass and aramid sewing threads are coated during manufacture with sizing's or finishes, including PTFE, to serve as aids in textile processing. When these products are heated above the continuous operating temperature of PTFE (550 degrees F, 287 degrees C), adequate ventilation and / or personal protective equipment must be used in accordance with site-specific exposure assessment as vapors can be emitted and may be hazardous if inhaled. See Safety Data Sheet or contact W.F. Lake Corp. for more information.