




High Performance PTFE & Silicone Coated Products

PTFE Coated Para-Aramid* Thread

500 deg. Fahrenheit



260 deg. Celsius



Product Data	
Product #	R722-80BLK
Thread Style	- Para-Aramid* Continuous Filament-
Coating Type	-PTFE, Sintered-
Min. Coating (%)	12
Yield (yds/lb)	3,750
Tensile (lbs)	30
Diameter (nom)	0.015"
Final Twist	-“Z”-
Color	-Black-
Serving Package: King Spool Operating Temp: Para-aramid to 500 deg. F	
Approx. Net Wt.: 1 lb/spool (others available)	
Available with high speed silicone thread lubricant applied in line.	
All values are typical and should not be used for writing specifications. *Kevlar Reg. DuPont	

W.F. Lake Corp.

P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936
www.wflake.com
info@wflake.com

Important Processing Information.

W.F. Lake Corp. PTFE coated fiberglass and aramid sewing threads are coated during manufacture with sizing's or finishes, including PTFE, to serve as aids in textile processing. When these products are heated above the continuous operating temperature of PTFE (550 degrees F, 287 degrees C), adequate ventilation and / or personal protective equipment must be used in accordance with site-specific exposure assessment as vapors can be emitted and may be hazardous if inhaled. See Safety Data Sheet or contact W.F. Lake Corp. for more information.