


PTFE Coated Round Braided Draw Cord

550 deg. Fahrenheit



287 deg. Celsius



Product Data					
Product Series	TFDC-		TLDC-	E790-Series	
Product #	-1875	-2187	-2500	-1875	-400 Kevlar*
Coating Type	PTFE, Sintered		PTFE, Unsintered**	Uncoated	
Braid Type	E-Glass		E-Glass	Para-Aramid	
Diameter (nom. in.)	0.14	0.19	0.24	0.14	
Tensile (lbs. min)	200	250	300	200	450
Standard Colors	Black, Natural, Gray		Orange, White	Gold/Natural	
Operating Temp	550 deg. F/287 deg. C			400F/204C	
Std. Package Size	500 (-2187, -2500); 650; 1000; 1250 (orange only) foot spools			1,000 ft spools	
Elongation: typically less than 5%		Operating Temp: See above			
Colors other than standard are available and may require minimum purchase quantity.				*Registered DuPont	
Spool Size is standard with 8.5" flange, 6.5" wide nominal.				** NASA Spec Top Coat	
All values are typical and should not be used for writing specifications.					

W.F. Lake Corp.

P.O. Box 4214
65 Park Road
Glens Falls, NY 12804
Customer Service: (800) 428-1162
Tel: (518) 798-9934
Fax: (518) 798-9936
www.wflake.com
info@wflake.com

Important Processing Information.

W.F. Lake Corp. PTFE coated fiberglass and aramid sewing threads are coated during manufacture with sizing's or finishes, including PTFE, to serve as aids in textile processing. When these products are heated above the continuous operating temperature of PTFE (550 degrees F, 287 degrees C), adequate ventilation and / or personal protective equipment must be used in accordance with site-specific exposure assessment as vapors can be emitted and may be hazardous if inhaled. See Safety Data Sheet or contact W.F. Lake Corp. for more information.