


## PTFE Coated Quartz Tie Cord

2000 deg. Fahrenheit - Fiberglass  
 550 deg. Fahrenheit - PTFE



1075 deg. Celsius - Fiberglass  
 287 deg. Celsius - PTFE



<b>Product Data</b>	
<b>Product #</b>	<b>Q761-540</b>
<b>Coating Type</b>	- PTFE, Unsintered -
<b>Braid Type</b>	-Round-
<b>Yield (yds/lb)</b>	345
<b>Thickness (in.)</b>	n/a
<b>Width (in.)</b>	n/a
<b>Diameter (in.)</b>	.050
<b>Tensile (lb/min)</b>	65
<b>Package Size (yds)</b>	250 Yds
<p><b>Elongation</b> of tie cord is typically less than 5%. <b>Operating Temps.</b> 2000 deg. F –Fiberglass / 550 deg. F –PTFE</p> <p><b>Colors</b> other than natural may require minimum purchase quantity. Approx. 25% tensile strength loss with colors. Please consult the factory.  <b>Dimensions</b> shown are nominal, however most are within 10%. Consult factory as needed.</p>	

**W.F. Lake Corp.**  
 P.O. Box 4214  
 65 Park Road  
 Glens Falls, NY 12804  
 Customer Service: (800) 428-1162  
 Tel: (518) 798-9934  
 Fax: (518) 798-9936  
[www.wflake.com](http://www.wflake.com)  
[info@wflake.com](mailto:info@wflake.com)

### Important Processing Information.

W.F. Lake Corp. PTFE coated fiberglass and aramid sewing threads are coated during manufacture with sizing's or finishes, including PTFE, to serve as aids in textile processing. When these products are heated above the continuous operating temperature of PTFE (550 degrees F, 287 degrees C), adequate ventilation and / or personal protective equipment must be used in accordance with site-specific exposure assessment as vapors can be emitted and may be hazardous if inhaled. See Safety Data Sheet or contact W.F. Lake Corp. for more information.